



26G

Excavator

- Net Power: 14.9 kW (20 hp)
- Max. Digging Depth 2.59 m (8 ft. 6 in.)
- Operating Weight: 2,770 kg (6,110 lb.)

Build Your Own

[Download Product Brochure >](#)

[Find a Dealer >](#)

[Compare to Competitors >](#)

Features

[Expand All](#)

+ Compact Design.

+ Tracks.

+ Ease of Control

+ Engine

+ Visibility

Show More

Specs & Compare

DRIVELINE

Engine Manufacturer	Yanmar
Number Of Cylinders (Per Engine)	3
Displacement, ltr (Inches ³)	1.267 (77)
Rated speed, rpm	2500
Engine Output - Net, kW (hp)	14.9 (20)
Track Shoe Width, mm (Inches)	300 (12)

DIMENSIONS

Transport Length Mono (Inches)	4180 (13 ft 9 in)
Transport Height - (Inches)	2430 (8 ft)
Overall Undercarriage Width, (Inches)	1500 (4 ft 11 in)
Track Length On Ground, mm (Inches)	1530 (5 ft)
Undercarriage Overall	1960 (6 ft 5 in)

Tailswing Radius, mm (ft/in)	800 (2 ft 7 in)
Ground Clearance, mm	300 (12)
Dozer Blade Height, mm	320 (12.6)
Dozer Blade Width, mm	1500 (4 ft 11 in)
Width over standard tracks, mm	1500 (4 ft 11 in)
Track Gauge, mm (ft/in)	1200 (3 ft 11 in)
Digging Reach - Mono Boom, mm	4630 (15 ft 2 in)
Dig Height - Mono Boom, mm	4280 (14 ft 1 in)
Dump Height - Mono Boom, mm	3040 (10 ft)
Dig Depth - Mono Boom, mm	2590 (8 ft 6 in)
Standard Dipper, mm (ft/in)	1170 (3 ft 10 in)

Show More

Compact Excavator Attachments



Augers & Trenchers



Hammers

[View All >](#)

Offers & Discounts

[Expand All](#)

+ 0% APR fixed rate for 36 Months on installment plan OR Big Cash Savings†

Product Brochures

Download Product Brochure
Construction Equipment Fleet Guide
Manuals

Parts & Maintenance

Remanufactured Parts & Components
Maintenance Videos

Operator Resources

Safety & Operation Videos
John Deere University
Simulators

Features and specifications are based on published information at the time of publication. Features and specifications are subject to change without notice.